

Reference data

Eaton 3S Mini 36W



Product	Eaton Ref	Short description
Eaton 3S Mini 36W	3SM36	Compact DC UPS with battery backup for Internet gateways, IP cameras, smart-home controllers, personal assistants, digital equipment, etc.... 4 x Barrel DC adaptors provided (3,5x1,3mm; 4,75 x 1,7mm; 5,5 x 2,1mm; 5,5 x 2,5mm).

Packaging	Size (W x D x H*, mm)	Weight (kg)	Shipping package	Bar Code
Individual Pack	163 x 192 x 57	0,7	1 product / pack	3553340705014
Transport Carton	600 x 196 x 248	8,5	12 packs / box	
Pallet	1200 x 1000 x 1100	450	480 packs / pallet (=40 transport boxes per pallet)	

Packaging content
DC UPS with Schuko input cord (1m) + 4 outputs DC adaptors + quick-start

Technical Specifications	
Electrical specifications	90-264V, 50-60 Hz
Power rating	36 W
Output voltage / current	9V/3A - 12V/3A - 15V/2,4A - 19V/1,89A
User interface	Voltage selection & battery level LED indicators
Installation	Require earth connection
Environment	For indoor, dry environment only
Colour	Black (RAL 9011) and white (RAL 9003)
Size (W x D x H)* / Weight	95.5 x 136 x 30mm / 0,4 kg
Warranty	2 years
Technical standards	CE Mark, Safety: IEC 62477-1: 2012-07, EN 62477-1: 2012-10 , CB report CEM : IEC 62040-2 : 2016-11, EN 62040-2 : 2018-09 Environment : IEC 62040-5-3

Typical use	Typical runtime
- Internet gateways - IP cameras - Personal assistants - Smart home gateways - Connected devices - VoIP phones	40 min for Internet gateways 120 min for IP cameras

Key selling points
- Ideal Protection for single DC voltage powered device - Up to 120 min runtime - Compact & attractive design - Led indicator for voltage setting and remaining battery level - 2 x 2200mAh lithium-ion battery - Standard and replaceable battery cell

* W x D x H = Width x Depth x Height

Reference data

Eaton 3S Mini 36W BS



Product	Eaton Ref	Short description
Eaton 3S Mini 36W BS	3SM36B	Compact DC UPS with battery backup for Internet gateways, IP cameras, smart-home controllers, personal assistants, digital equipment, etc.... 4 x Barrel DC adaptors provided (3,5x1,3mm; 4,75 x 1,7mm; 5,5 x 2,1mm; 5,5 x 2,5mm).

Packaging	Size (W x D x H*, mm)	Weight (kg)	Shipping package	Bar Code
Individual Pack	163 x 192 x 57	0,7	1 product / pack	3553340705021
Transport Carton	600 x 196 x 248	8,5	12 packs / box	
Pallet	1200 x 1000 x 1100	450	480 packs / pallet (=40 transport boxes per pallet)	

Packaging content
DC UPS with BS input cord (1m) + 4 outputs DC adaptors + quick-start

Technical Specifications	
Electrical specifications	90-264V, 50-60 Hz
Power rating	36 W
Output voltage / current	9V/3A - 12V/3A - 15V/2,4A - 19V/1,89A
User interface	Voltage selection & battery level LED indicators
Installation	Require earth connection
Environment	For indoor, dry environment only
Colour	Black (RAL 9011) and white (RAL 9003)
Size (W x D x H)* / Weight	95.5 x 136 x 30mm / 0,4 kg
Warranty	2 years
Technical standards	CE Mark, Safety: IEC 62477-1: 2012-07, EN 62477-1: 2012-10 , CB report CEM : IEC 62040-2 : 2016-11, EN 62040-2 : 2018-09 Environment : IEC 62040-5-3

Typical use	Typical runtime
- Internet gateways - IP cameras - Personal assistants - Smart home gateways - Connected devices - VoIP phones	40 min for Internet gateways 120 min for IP cameras

Key selling points
- Ideal Protection for single DC voltage powered device - Up to 120 min runtime - Compact & attractive design - Led indicator for voltage setting and remaining battery level - 2 x 2200mAh lithium-ion battery - Standard and replaceable battery cell

* W x D x H = Width x Depth x Height